



Andor



Kjell



Oskar

Designed by

Kees Jacobs



Faber Special Wood 2014-2015

	Andor	Kjell	Oskar
Norm vermogen (kW) Heat Output Leistung Puissance	7 kW	8 kW	8 kW
Rendement Output Wirkungsgrad Rendement	78%	78%	78%
Gewicht-staaluitvoering Weight Gewicht-Stahlmantelausführung Aplomb	129 kg	102 kg	111 kg
Massaastroom Mass flow Abgasmassenstrom Flux de masse	7 g/s	7,6 g/s	7 g/s
Externe luchttoevoeraansluiting External air-inlet Externe Frischluftzufuhr Apport d'air extérieur	√	√	√
Rookgastemperatuur Flue gas temperature Abgastemperatur Température des gaz de fumée	280 °C	213 °C	268 °C
Gekeurd volgens Tested according Geprüft nach Testé selon	DIN EN 13240 2005	DIN EN 13240 2005	DIN EN 13240 2005
Airwash systeem Air-wash system Air-wash system Système Air-wash	√	√	√
Bovenaansluiting/ achter aansluiting Top connection / Back connection Abgang oben / Abgang hinten Raccordement au-dessus / sortir arrière	150 mm	150 mm	150 mm
CE-gekeurd CE approved CE geprüft Certifié CE	√	√	√
Zwart/grijs Black/grey Schwarz/grau Noir/gris	√	√	√

Glen Dimplex Benelux BV
Saturnus 8
NL-8448 CC Heerenveen
PO Box 219
NL-8440 AE Heerenveen
t +31 (0)513 656 500
f +31 (0)513 656 501
e info@faber.nl
i www.faber.nl

Glen Dimplex Benelux BV
Vestiging België/ Adresse Belgique
Burgemeester Maenhoutstraat 64
B-9820 Merelbeke
t +32 (0)9 210 02 10/210 02 11
f +32 (0)9 210 02 12
e info@faber.be
i www.faber.be

Faber Deutschland
Vertriebsbüro Project 1711 GmbH & Co. KG
Im Gewerbegebiet 12
D-48612 Horstmar
t +49 (0)2558 9973880
f +49 (0)2558 9973881
e info@faber-kamine.de
i www.faber-kamine.de